



SPECIFICATIONS

| Model | LA300 | LA400 | LA600 | LA800 |
|-----------------------|-----------------------------------------|--------------------------|--------------------------|--------------------------|
| Stereo power 8 Ω | 300W | 400W | 600W | 800W |
| 1KHz 0.1% THD 4 Ω | 450W | 600W | 900W | 1200W |
| 2 Ω | ---- | 800W | 1100W | 1400W |
| Bridge mono power 8 Ω | 700W | 1000W | 1800W | 2000W |
| 1KHz 0.1% THD 4 Ω | ---- | 1200W | 2000W | 2400W |
| Signal to noise | 103dB | 105dB | 105dB | 106dB |
| Slew rate | 60v/μS | 60v/μS | 80v/μS | 80v/μS |
| Damping factor | 400:1 | 450:1 | 500:1 | 550:1 |
| Frequency response | +/-0.1dB, 20Hz + 20kHz | | | |
| THD | ≤ 0.01% Rated Power@ 8 Ω 1kHz | | | |
| IMD | ≤ 0.01% Rated Power @ 8 Ω | | | |
| Input sensitivity | 0.775V, 1.0V, 1.55V | | | |
| Input impedance | 10K/20K ohms, unbalanced or balanced | | | |
| Input CMRR | ≤ -75dB | | | |
| Cross talk | ≤ -70dB | | | |
| LEP indicator | Signal, Protect, Deceive, Clip/Limiting | | | |
| Main power supply | -220V 50/60Hz FUSE: T8A | -220V 50/60Hz FUSE: T10A | -220V 50/60Hz FUSE: T12A | -220V 50/60Hz FUSE: T15A |
| Net weight | 16kg | 17kg | 22kg | 23kg |
| Dimensions (mm) | 483Wx420Dx88H | | 483Wx490Dx88H | |