



## SPECIFICATIONS

Model	SPT6001	SPT7001	SPT8001	SPT9001
Stereo power 8 Ω	350W	550W	700W	900W
1KHz 0.1% THD 4 Ω	600W	900W	1100W	1500W
2 Ω	850W	1300W	1700W	2200W
Bridge mono power 8 Ω	1200W	1800W	2200W	3000W
1KHz 0.1% THD 4 Ω	1700W	2600W	3400W	4400W
Signal to noise	103dB	105dB	105dB	106dB
Slew rate	60v/μS	60v/μS	80v/μS	80v/μS
Damping factor	400:1	450:1	500:1	550:1
Frequency response	+/-0.1dB, 20Hz + 20kHz			
THD	≤ 0.01% Rated Power@ 8 Ω 1kHz			
IMD	≤ 0.01% Rated Power @ 8 Ω			
Input sensitivity	0.775V, 1.0V, 1.55V			
Input impedance	10K/20K ohms, unbalanced or balanced			
Input CMRR	≤ -75dB			
Cross talk	≤ -70dB			
LEP indicator	Signal, Protect, Dective, Clip/Limiting			
Main power supply	-220V 50/60Hz FUSE: T8A	-220V 50/60Hz FUSE: T10A	-220V 50/60Hz FUSE: T15A	-220V 50/60Hz FUSE: T20A
Supply power	1050W	1650W	2100W	2700W
Net weight	16kg	18kg	30kg	31kg
Dimensions (mm)	483Wx418Dx88H		483Wx418Dx133H	